

O = 715 ; M = 670 ; A = 715 mm

**MATERIAL**  
150 kp dleeved Dyneema

**INFOS**

**KATEGORIE**

- Beginner
- Advanced
- Master
- Allround
- Trick
- Traction
- Precision
- Freestyle
- Team
- Low Wind

**WINDBEREICH**

12 - 40	KM/H	20	KM/H
7 - 25	MPH	12	MPH
3 - 6	BFT.	4	BFT.
6 - 22	KNOT.	11	KNOT.

**OPT. WIND**






**SCHNUR**

80 - 120	kp	25 - 35	m
170 - 260	lbs	80 - 115	ft

**FRAME**

ITEM NUM.	MOUNTING POSITION	ITEM NAME	#	LENGTH
	Spine	Ø8 mm fibergals tube	1	
	Upper Spreader	Ø8 mm fibergals tube	1	
	Lower Spreader	Ø8 mm fibergals tube (+80mm plug)	2	
	Upper LE	Ø8 mm fibergals tube (+80mm plug)	2	
	Lower LE	Ø8 mm fibergals tube (+80mm plug)	2	
	Sailbatten	Ø3 mm fiberglas rod	2	
	Standoff	Ø3 mm fiberglas rod	2	
	Plugs	Ø6 mm fiberglas rod	10	

**ABMESSUNGEN**

	cm	inch	<b>SPEED</b> 
218	85,8		
	cm	inch	<b>POWER</b> 
94	37		
	g	oz	
489	17,2		

**HINTS & TIPPS**

**SAIL MATERIAL**

70D RipStop-Polyester

**INCLUDED ACCESSORIES**

**PRODUCT INTRODUCTION**

**PRODUCT CLEARING**

Februar 2017

**PARTS**

ITEM NUM.	MOUNTING POSITION	ITEM NAME	#
	Leadingedge/Spine	Endcap 8 mm	4
	Leadingedge	Leading egdge connector 8 mm	4
	Spine	Centre T 8 mm	1
	Leadingedge	Splitnock 8 mm	2
	Leading Edge & Spine	Stopper clip 8 mm	7
	Lower Spreader	Stnadoff connector big	2
	Standoff	Endcap 3 mm	8
	Leadingedge	Ferrule 8 mm	2