



O=48 M=62,5 A=54 S=16,5

**MATERIAL**  
Sleeved Dyneema 96 kp, gray

**INFOS**

**CATEGORY**

- Beginne
- Advance
- Master
- Allroun
- Trick
- Traction
- Precision
- Freestyl
- Tea
- Low

**WIND RANGE**

12 - 49 KM/H	20 KM/H
7 - 30 MPH	12 MPH
3 - 6 BFT.	4 BFT.
6 - 26 KNOT.	11 KNOT.

**OPT. WIND**

**FLYING LINE**

50 - 100 kp	20 - 35 m
110 - 210 lbs	65 - 115 ft

**DIMENSIONS**

	cm	inch
	204	80,3
	112	44,1
	g	oz
	315	11,1



**HINTS & TIPPS**

**SAIL MATERIAL**

VENTEX Polyester

**INCLUDED**

PRODUCT INTRODUCTION — PRODUCT CLEARING

**FRAME**

ITEM NUM.	MOUNTING POSITION	ITEM NAME	#	LENGTH
a60075	leading Edge	Kohlefaser AVIA .2300 0,75m	4	75
a60082	Spine	Kohlefaser AVIA .2300 0,82m	1	82,5
a60050	upp. spreader	Kohlefaser AVIA .2300 0,50m	1	50
a60075	low. spreader	Kohlefaser AVIA .2300 0,75m	2	72,5
a20100	inner standoff	Microcarbon AVIA .080 1m	2	23
a20100	mid. standoff	Microcarbon AVIA .080 1m	2	21
a20100	outer standoff	Microcarbon AVIA .080 1m	2	18,5

**PARTS**

ITEM NUM.	MOUNTING POSITION	ITEM NAME	#
135988	upper and lower leading	G-Force APA Connector "B"	4
153660	Wingtip	HQ-nock 6mm	2
135914	Center T	Avia alu-sleeve `230/5,9mm	1
153407	Center T	HQ connector 5,9mm	1
150660	Spinetip	PE-tube, black 6/3mm	1
153416	Standoff/Spreader	standoff connector 5,5-6,3mm	6
153412	Standoff/Sail inner	standoff clip 2mm	2
153410	Standoff/Sail mid.	standoff clip 2mm	2
153410	Standoff/Sail outer	standoff clip 2mm	2
135914	Leading edge	Avia alu-sleeve `230/5,9mm	2
135979	low. spreader	plug f. 0.230 6mm - 10cm	2
153490	Spine/Upper Spreader	rubber ring 10/4mm	1