



O = 495 mm | M = 615 mm | A = 470 mm

**MATERIAL**

60 daN corded Dyneema line

**INFOS**

**KATEGORIE**

- Beginner
- Advanced
- Master
- Allround
- Trick
- Traction
- Precision
- Freestyle
- Team
- Low Wind

**WINDBEREICH**

6 - 35	KM/H	22	KM/H
4 - 22	MPH	14	MPH
2 - 5	BFT.	4	BFT.
3 - 19	KNOT.	12	KNOT.

**OPT. WIND**

**SCHNUR**

40 - 80	kp	20 - 30	m
80 - 170	lbs	65 - 95	ft

**ABMESSUNGEN**

cm	inch
240	94,5
90	35,4
g	oz
300	10,6

**SPEED**

0 100

**POWER**

0 100

**HINTS & TIPPS**

**SAIL MATERIAL**

ICAREX PC31 Ripstop Polyester

**INCLUDED ACCESSORIES**

**PRODUCT INTRODUCTION** — **PRODUCT CLEARING**

Februar 2018

**FRAME**

ITEM NUM.	MOUNTING POSITION	ITEM NAME	#	LENGTH
	Upper Spreader	ø6 mm Carbon Tube	1	520
	Lower Spreader	SkyShark black Diamond Nitro std	2	697
	Spine	SkyShark P-300	1	805
	Upper LE	SkyShark 3PT	2	745
	Lower LE	SkyShark 3PT	2	735
	Inner Standoff	Ø3 mm solid CFK	2	225
	Outer Standoff	Ø3 mm solid CFK	2	230
	Plug Lower Spreader	Ø 0.285" solid carbon	1	100
	Plug Leadingedge	Ø 0.240" solid carbon	2	80

**PARTS**

ITEM NUM.	MOUNTING POSITION	ITEM NAME	#
	Spine/Lower Spreader	T-Piece	1
	Leadingedge	HQ Leadingedge Connector ø6/6	4
	Standoff/Spreader	HQ Standoff Connector 5.5 - 6 mm	4
	Standoff / Sail	Standoff Clip, screwable ø3 mm	4
	Spinetip	Trim Weight 20g (incl. End Fitting)	1
	Spine Nose	Endcap ø6 mm	1
	Upper LE	Endcap ø6 mm	2
	Leadingedge	Yoyo-Stopper ø8 mm + cable tie	2
	Lower LE	HQ Split Nock ø6 mm	2
		Stopper Clips ø6 mm	12